




Product name — CHRBOTTRAP/CHSQBOTTRAP



Please note: Image is for illustrative purposes only and may differ slightly to the actual product.

- **Single-person assembly**
- **We always recommend using professional tradespeople to install your product**

V1_14.10.2023

1

Congratulations on your purchase And welcome to our growing gang of savvy shoppers

We're on a mission to bring you extraordinary bathroom products, for less. From modern to traditional style ceramics, plus the gorgeous fixtures, fittings and furniture to match. So, you can fall in love with your space every single day .

As one of the UK's largest independent bathroom stores, we've received countless awards; including the National Business Awards UK, the Digital Entrepreneur Awards and being placed on The Sunday Times Fast Track 100.


We hope your new product exceeds your highest expectations. However, if you experience any problems, please:

- log in to your account and contact our customer services team via your self-serve portal betterbathrooms.com/CustomerAccount/Login.
- contact us via betterbathrooms.com/content/contact-us.

Important information

- Please read these instructions thoroughly and retain for future reference
- Manufactured to EN274 traps for sanitary appliance

Parts




Disassemble all the parts according to the figure above.

Please note that Parts are for illustrative purposes only and may differ slightly to the actual product


- | | |
|----------|---------|
| 1.WASHER | 4.Nut |
| 2.BODY | 5.PIPE |
| 3.WASHER | 6.Cover |

2


Installation



Step1: Put washer,nut and cover on the pipe,then connect pipe to the body.




Step2: Loosen the nut, and then pull the body to adjust up and down, so that the outlet of the body is in line with the drainage hole. Insert the pipe into the drainage hole, put the washer into the body, install it on the click clack basin waste, and then tighten the seal.



Step3: Apply sealant between drainage hole and pipe,tighten the nut. After the sealant solidifies, pour the water into the basin for drainage, test for water leakage, and finally install the decorative cover on the wall.

3



Step4: : Installation is completed.

Maintenance

To maintain the surface finish of your product, wipe clean after every use, using a cleandamp cloth, a mild detergent mixture can be used. Do not use abrasive cleaning agents or materials on the product surface.

If any harsh chemicals come into contact with the surface of the product during bathroom cleaning, rinse off immediately, wipe clean and dry

For more information

- visit betterbathrooms.com
- email customerservices@buyitdirect.co.uk
- call 03303903062
- write to Trident Business Park, Neptune Way, Huddersfield, HD2 1UA

4