USER MANUAL



Thank you for choosing Better Bathrooms.

Please read this manual before installing your product and keep for future reference.




Product

Arissa Mini Cloakroom Basin Mixer Tap - ARIMB001, ARIBB001, ARICH001, ARIMW009, ARIVRG001, AR2TCBM

Arissa Mono Basin Mixer Tap - ARIMB002, ARIBB002, ARICH002, ARIMW001, ARIVRG002, AR2TMBM

Arissa Mono High Rise Basin Mixer Tap - ARIMB003, ARIBB003, ARICH003, AR2TTALLBM, ARVRGTALL



- Single-person assembly
- Tools required
- We always recommend using professional tradespeople to install your product

Congratulations on your purchase

And welcome to our growing gang of savvy shoppers

We're on a mission to bring you extraordinary bathroom products, for less. From modern to traditional style ceramics, plus the gorgeous fixtures, fittings and furniture to match. So, you can fall in love with your space every single day.

As one of the UK's largest independent bathroom stores, we've received countless awards; including the National Business Awards UK, the Digital Entrepreneur Awards and being placed on The Sunday Times Fast Track 100.

We hope your new product goes above and beyond your expectations. However, should any problems occur, please:

- log in to your account and contact our customer services team via your self-serve portal – <u>betterbathrooms.com/CustomerAccount/Login</u>
- contact us via <u>betterbathrooms.com/content/contact-us</u>

Important information

- Please read these instructions thoroughly and retain for future reference
- Installation must be carried out in compliance with The Water Fittings Regulations and Scottish Water Byelaws.
- The system must be flushed prior to installation.

SKU Number	Minimum working pressure	Maximum working pressure
ARIMB001/ARIBB001/ARICH001/ARIM W009/ARIVRG001/ AR2TCBM-2	1.5 bar	5 bar
ARIMB002/ ARIBB002/ ARICH002/ ARIMW001/ ARIVRG002/ AR2TMBM/ ARIMB003/ARIBB003/ARICH003/ AR2TTALLBM/ARVRGTALL	1 bar	5 bar


- Pressures must be equal for optimum performance
- Please do not connect hot and cold water supply lines in reverse. This could result in hot water flowing from cold line and cause scalding.
- The feed-water temperature of water shall not exceed 85°C.

Exceeding 85°may cause scalding, the service life of faucets might be shortened, or the faucet might be damaged.

• After installation, please make sure the faucet is securely mounted and checked for leaks.


Parts / Diagrams


Round Mini Cloakroom Basin Mixer Tap			
	No	Description	
	1	Handle assembled	
2 3	2	Dome	
	3	Locknut	
□	4	Cartridge	
	5	Body assembled	
	6	Aerator with housing	
	7	Rubber washer	
*** D	8	Gasket	
3	9	Leg	
	10	Locknut	
8.8	11	Screw	
	12	Flexible hose	




Round Mono High Rise Basin Mixer Tap			
<u></u>	No	Description	
	1	Handle assembled	
3	2	Dome with locknut	
4	3	Cartridge	
5	4	Body assembled	
	5	Aerator with housing	
	6	Rubber washer	
	7	Gasket	
	8	Leg	
9	9	Locknut	
	10	Screw	
급급	11	Flexible hose	

Dimensions









Tools required

Screwdriver

Installation






Connect the hot and cold flexible hoses to the isolation valves (not included), hot on the left, cold on the right.

Turn on water supply and check for leaks.

Operation




By lifting the Lever Handle upwards, the valve will be activated. Water flow will increase by continuing to lift up the Lever Handle. By rotating the Lever Handle counter-clockwise, the water temperature will decrease. By rotating the Lever Handle clockwise, the water temperature will increase.

Troubleshooting

Issues	Inspection Item		
	Mini Cloakroom Basin Mixer Tap	Mono Basin Mixer Tap	
Poor water flow	 Is the mixer cartridge(4) free from debris Is there blockage within the filter mesh on aerator(6) Is the flexible hose(12) kinked or twisted Was the system flushed prior to installation 	 Is the mixer cartridge(3) free from debris Is there blockage within the filter mesh on aerator(5) Is the flexible hose(11) kinked or twisted Was the system flushed prior to installation 	
Water leak	 Is the locknut(3) on top of cartridge fully tightened Is there damage or dirt within the O-rings of the cartridge(4) Is there damage or dirt with the rubber washer or O-ring of the aerator(6) Is the housing of aerator(6) fully tighten Is there damage with the rubber washer(7) Is there damage within the rubber washer inside the nuts of flexible hoses(12) Is there damage with the O-rings on the flexible hoses(12) 	 Is the locknut(2) on top of cartridge fully tightened Is there damage or dirt within the O-rings of the cartridge(3) Is there damage or dirt with the rubber washer or O-ring of the aerator(5) Is the housing of aerator(5) fully tighten Is there damage with the rubber washer(6) Is there damage within the rubber washer inside the nuts of flexible hoses(11) Is there damage with the O-rings on the flexible hoses(11) 	
Handle loose	Is the screw inside the handle (1) fully tightened	Is the screw inside the handle (1) fully tightened	
Body loose	Are the locknut(10) and screw(11) underneath fully tightened	Are the locknut(9) and screw(10) underneath fully tightened	

Maintenance

Replacement of Cartridge Round Mini Cloakroom Basin Mixer Tap A: Uninstall the lever by rotating anticlockwise. Remove the screw by using allen key. Take out the handle. B: Remove the Cap, locknut(by using wrench), cartridge from the body accordingly to the graph. Install a new cartridge in reverse steps. Round Mono Basin Mixer Tap A: Uninstall the lever by rotating anticlockwise. Remove the screw by using allen key. Take out the handle. B: Loose the Cap with locknut by using a plier to clamp the blocks inside and rotate anti-clockwise, take out the cap and cartridge from the body accordingly to the graph. Install a new cartridge in reverse steps.



Cleaning

To maintain the surface of your product, wipe with a clean damp cloth and wipe dry, do not use any abrasive cleaning agents or materials. If any harsh chemicals come into contact with the surface of the product, rinse and wipe clean immediately.

For more information

- · visit betterbathrooms.com
- email customerservices@buyitdirect.co.uk
- call 03303903062
- write to Trident Business Park, Neptune Way, Huddersfield, HD2 1UA



Part of the BuyltDirect Group