# **USER MANUAL**



Thank you for choosing Better Bathrooms.

Please read this manual before installing your product and keep for future reference.



## ROUND FRONTLIT TOUCH FRAME LED MIRROR – NYX



NYXBB600 NYXBB800 – 600/800mm Brushed Brass NYXMB600 NYXMB800 – 600/800mm Matt Black

- FRAME TOUCH SENSOR CONTROL
- IP44 INGRESS PROTECTION
- LED LIGHT

#### **CONGRATULATIONS ON YOUR PURCHASE**

Our aim at Better Bathrooms is to bring you extraordinary bathroom products for less.

If you're after a modern, traditional, or totally unique bathroom style, we have the fittings and fixtures to bring your ideas to life so you can fall in love with your space every day.

We hope your new product goes above and beyond your expectations. However, should any problems occur, please:

- Log in to your account and contact our customer services team via your self-service portal betterbathrooms.com/CustomerAccount/Login
- Contact us via betterbathrooms.com/contact/contact-us


## **CONTENTS**

SAFETY	3
BATHROOM ZONES	4
PARTS SUPPLIED	4
TOOLS REQUIRED	5
PRODUCT OVERVIEW	5
INSTALLATION DIMENSIONS	6
INSTALLING THE MIRROR	7
OPERATION	8
CLEANING AND MAINTENANCE	8
TECHNICAL SPECIFICATIONS	8

#### SAFETY


- A qualified electrician should install this mirror.
- This fitting is only suitable for connection to a 220-240V earthed supply in accordance with current IEE wiring regulations and should be installed in accordance with local Building Regulations.
- This is for domestic, indoor use only.
- The fitting should be connected to a dedicated lighting circuit, which must be protected by a 5-amp fuse (or a 6-amp miniature circuit breaker).
- Before installing the fitting, ensure the mains supply is switched off and that the
  appropriate fuse is removed (or the appropriate circuit breaker is switched off) before
  commencing installation. Ensure that measures are taken to prevent the supply from
  being inadvertently reconnected.
- If there is a "Minimum Distance" Label, please do not allow Flammable Materials to rest within that distance from the unit.
- This product may contain delicate parts be careful during handling and maintenance to avoid breakage.
- Any modification to the fitting will invalidate the warranty and may render the product unsafe.
- A defective appliance may cause electric shock. Never switch on a defective or damaged appliance. Disconnect the appliance from the mains before seeking assistance.
- This product is IP44 rated, and no part of the installation is allowed to be within bathroom Zones 0 or 1. Installation is permitted within Zone 2.
- This product must be earthed. Before commencing installation, ensure that there are no pipes or wires located behind the wall that may be damaged during drilling.
- Ensure that the hanging location has been decided upon and marked clearly to avoid unwanted damage to the wall due to incorrect positioning.
- Check that the mirror is not damaged prior to installation.
- Take care of unpacking, and do not use a sharp blade to open it as this may damage the mirror and void your warranty.
- Installation must only be carried out by a qualified professional or electrician.
- Once installed, silicon can be applied between the cabinet and the wall around the unit. Don't seal the bottom of the cabinet, as this may allow water to accumulate behind it.
- If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similarly qualified person in order to avoid a hazard.
- The light source of this luminaire is not replaceable; when the light source reaches its end of life, the whole luminaire shall be replaced.
- To reduce the risk of strangulation, the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

## **BATHROOM ZONES**




Zone 0:	The interior of the bathtub or shower basin.	
<b>Zone 1</b> : The area around the bathtub or shower basin up to a height of 2.25m above the floor		
Zone 2: The area stretching to 0.6m outside the bath or shower above the bath or shower if over 2.25m		

## **PARTS SUPPLIED**




**PLEASE NOTE:** It is the installer's responsibility to ensure that the fittings are suitable for the type of wall. Alternative fittings may be required (Not Supplied). If unsure, professional advice should be sought.

## **TOOLS REQUIRED**




## **PRODUCT OVERVIEW**



## **INSTALLATION DIMENSIONS**

## NYXBB600 NYXMB600 350 46 280 Wall-mount bracket Demist pad Demist pad 100 170 LED light Supply cord length: 600mm Aluminum frame Electronic box 59.5 Touch switch Back view Front View

## NYXBB800 NYXMB800



#### **INSTALLATION**


**IMPORTANT:** Before commencing installation, ensure that there are no pipes or wires located behind the wall that you will be drilling into.

The product dimensions are on the last page; alternatively, you can use the two hanging hooks on the back of the mirror as a guide.

- Ensure that the hanging location has been decided upon and marked clearly to avoid unwanted damage to the wall due to incorrect positioning.
- Check that the mirror is not damaged prior to installation.
- Take care of unpacking, and do not use a sharp blade to open it, as this may damage the mirror and void your warranty.

**IMPORTANT:** The power must be disconnected when installing and performing any maintenance.

- 1. Mark the drill hole spots on your wall using a spirit level to ensure they are level.
- 2. Drill the holes in the wall with an 8mm drill bit and insert two wall plugs.
- 3. Insert the screws, leaving these protruding by 3mm. It is recommended that these levels be checked again with the spirit level.
- 4. Connect the mirror to your electrics via a fuse spur following all local regulations and the wiring diagram provided. Then, turn the power back off via the installed switch.
- 5. Hang the mirror onto the screws. Re-connect the power.



## **OPERATION**

Your mirror has a touch switch towards the base of the mirror. Tap it once to turn on the lights and the demister. Tap again to turn off the lights and demister.



Hold down the button to change the lights from cool white to warm white and back again.

## **CLEANING AND MAINTENANCE**

Never use products containing bleach or abrasive cleaners, as this will have a detrimental effect on the appearance and lifespan of the product.

Use a clean microfibre cloth to clean the mirror.

## **TECHNICAL SPECIFICATION**

Model	NYXBB600	NYXBB800
Model	NYXMB600	NYXMB800
WxHxD (mm)	600x600x60	800x800x60
Net Weight (Kg)	3.9	6.8
Power Cord length (mm)	600	800
Rated Power (W)	25W	35W
IP Rating	IP 44	
Input	220 V-240 V 50 Hz	

This product contains a light source of energy efficiency class F and must only be replaced by a professional or similarly qualified person.



#### **DISPOSAL**

Recycling facilities are now available for all customers at which you can deposit your old electrical products. Customers will be able to take any old electrical equipment to participating sites run by their local councils.

Please remember that this equipment will be further handled during the recycling process, so please be considerate when depositing your equipment. Please get in touch with the local council for details of your local household waste recycling centres.



At the time of printing the product contains no substances listed within Annex XIV of the Reach Regulations (EC) 1907/2006. In accordance with Article 59 of the same regulation, the following substances are contained within the product at permitted levels: Cadmium.

As a responsible manufacturer, we monitor the regulations to ensure continued compliance. Further information can be provided upon request.

#### For more information

- · visit betterbathrooms.com
- email support@betterbathrooms.co.uk
- call 0330 390 3062
- write to Trident Business Park, Neptune Way, Huddersfield, HD2 1UA

