


USER MANUAL



Thank you for choosing Better Bathrooms.
Please read this manual before installing your product
and keep for future reference.

better
bathrooms

Product-Wall Mounted Bath and Basin Tap



Please note: Image is for illustrative purpose only and may differ slightly to the actual product.

- Single-person assembly
- We always recommend using professional tradespeople to install your product

V1-20.04.2024

Congratulations on your purchase

And welcome to our growing gang of savvy shoppers

We're on a mission to bring you extraordinary bathroom products, for less. From modern to traditional style ceramics, plus the gorgeous fixtures, fittings and furniture to match. So, you can fall in love with your space every single day.

As one of the UK's largest independent bathroom stores, we've received countless awards; including the National Business Awards UK, the Digital Entrepreneur Awards and being placed on The Sunday Times Fast Track 100.

We hope your new product exceeds your highest expectations. However, if you experience any problems, please:

- log in to your account and contact our customer services team via your self-serve portal [betterbathrooms.com/CustomerAccount/Login](https://www.betterbathrooms.com/CustomerAccount/Login).
- contact us via [betterbathrooms.com/content/contact-us](https://www.betterbathrooms.com/content/contact-us).

Important information

- Please read these instructions thoroughly and retain for future reference.
- All installation work must be carried out to comply by a qualified installer.
- Always check pressure compatibility, check website for min/max pressure of product.
- Pressures to hot and cold supplies should be balanced for optimum performance.
- All installation work must be carried out to comply with the Water Bylaw Regulations.
- Isolation valves should be fitted to both supply pipes as part of the installation
- System must be flushed through prior to installation.
- The area should be checked for pipes and wires before drilling.



Flow Rates

Bar	0.1	0.2	0.5	1	1.5	2
L/Min	4.3	5.9	9.1	12.8	15.6	18

Guarantee

- Please check our website for individual product guarantee's.
- Some parts of the product, i.e. cartridge, are covered by a 12-month guarantee.
- Your guarantee can be invalid if the pre-installation checks are not carried out, installation is not carried out as per this guide, and correct maintenance instructions are not followed. Please see our website for T & C's.



Parts / Diagrams



Tools required



- Spanner

Installation



1. Determine the fixing position for the faucet body. Make a recess in the wall according to the size of the faucet body. The dimension of the groove should be 200mm x 70mm.


2. Place the mixer into the recess and mark the drill hole positions. Drill the holes in the wall recess. Prepare the hot and cold water supply pipes with correct fittings to connect to the mixer inlets as shown a suitable sealing method should be used on the pipes.




3. Insert the wall plugs into the drilled holes.

Place the mixer into position and secure using the screws provided. Connect the water supply pipes and tighten and ensure to use a suitable sealing method.


Turn on the water supply and check for leaks before fitting the cover plate.



5. Finish wall as required, still allowing access to the mixer.




6. Apply some adhesive sealant on the back of the face plate, and stick it on to the wall.



7. Install the spout to the valve with screws and check if there is any leakage. And then install the handle to the valve with screws and put back the cover cap. Installation complete.

OPERATION




Lift up the handle to open, turn left to hot water, turn right to cold water, and mix cold and hot water in the middle.

Maintenance

Cartridge removal

IMPORTANT: Ensure to turn off the water supply to the mixer prior to any maintenance
Please note: Design may vary from those shown below



1. Remove screw cap cover .
2. Loosen grub screw using a hex key.
3. Pull handle from the mixer.
4. Unscrew cartridge shroud.
5. Using a spanner remove cartridge nut.
6. Pull the cartridge from the mixer.
7. Carry out maintenance.
8. Replace cartridge ensuring to locate pins on the underside of the cartridge with holes inside the mixer.
9. Replace all components (do not overtighten cartridge nut).

CLEANING

To maintain the surface of your product, wipe with a clean damp cloth and wipe dry. Do not use abrasive cleaning agents or materials which can strip and scratch the surface; the use of these agents or materials can invalidate your guarantee. It is recommended to wipe and dry on a regular basis.

For more information

- visit [betterbathrooms.com](https://www.betterbathrooms.com)
- email customerservices@buyitdirect.co.uk
- call 03303903062
- write to Trident Business Park, Neptune Way, Huddersfield, HD2 1UA.

better
bathrooms

Part of the BuyItDirect Group